



Electrostatic Spray Manifold

Dryer Release Agent

Spray Control Benefits In Dryer Applications

- Reduce moisture levels
- More shelf stable.
- Crispier and crunchier product

ES2500 Spray Control Panel (1)

- Control the electric spray manifold
- Properly controls flow and alarms

Electrostatic Spray Manifold (2)

- Improves product quality with uniform coating
- Reduces misting and over spray
- Easy to maintain
- Flow rates ranging from 6-180 cc/min

Electrostatic Fluid Delivery (3)

- 15 Gal tank on cart
- 3-way outlet valve to direct fluid to the pump/drain port
- The pump assembly; pump max flow of 10 GPH, motor driven pump, 100-mesh strainer on the pump outlet.

High Voltage Power Supply Enclosure (4)

- High voltage power supply to manifold
- Allows for appropriate electrostatic voltage to get the best performance

Level Sensor Kit (5)

- Displays the current tank level as a percent to full
- Alarms at low level

DESCRIPTION:		 Spraying Systems Co. Spray Nozzles and Accessories P.O. Box 7900 - Wheaton, IL 60189-7900	
Dryer Release Agent SCS Series			
REVISION NO.	2	Data Sheet No.	
Revision Date:	5/10/23	Dryer Release Agent - SCS Series	
SHEET: 1 OF 1		DWG SIZE: B	